

What is claimed is:

1 1 (currently amended). A shower support comprising
2 a shower head and a hose,
3 a mounting fixture for mounting the support such that the support is
4 adjustable,
5 a pivotable arm jutting out of the mounting fixture, said arm having a
6 first end connected to the mounting fixture and a second opposite end, with a
7 water conduit extending from the mounting fixture to at least one additional
8 shower fixture attached along said arm,
9 a receptacle adapted to receive the shower head when the shower
10 head is not in hand operation, said receptacle being arranged at said second
11 opposite end of the arm away from the mounting fixture, wherein the shower
12 head and the receptacle are configured to allow the shower head to be
13 removed from the receptacle during hand operation of the shower head on the
14 hose, ~~and~~
15 wherein the shower head is supplied with water by the hose and
16 wherein the additional shower fixture is arranged to be supplied with water by
17 the water conduit independently of the shower head, and,
18 wherein the shower hose leads from the mounting fixture to a
19 handgrip of the shower head.

Claim 2 was canceled.

1 3(previously presented). The shower support according to claim 1,
2 wherein the water conduit is defined by a channel that extends through the
3 arm and leads to the additional shower fixture.

1 4(previously presented). The shower support according to claim 1,
2 wherein the arm comprises a length of hollow, profiled stock, at least from the
3 mounting fixture to the additional shower fixture.

1 5(currently amended). The shower support according to claim 1,
2 wherein the additional shower fixture is arranged between the mounting fixture
3 and ~~a the~~ far end of the arm **remote from the mounting fixture**.

Claim 6 is canceled.

1 7(previously presented). The shower support according to claim 1,
2 wherein the additional shower fixture is mounted on a side of the arm jutting
3 from the mounting fixture.

1 8(previously presented). The shower support according to claim 1,
2 wherein at least one said additional shower fixture is mounted on a underside
3 of the arm jutting from the mounting fixture.

1 9(previously presented). The shower support according to claim 1,
2 having multiple said additional shower fixtures and wherein the water conduit
3 provides a water supply common to all the additional shower fixtures.

1 10(previously presented). The shower support according to claim 1,
2 wherein the additional shower fixture is nondetachable.

Claim 11 was canceled.

1 12(previously presented). The shower support according to claim 1,
2 wherein the arm is pivotable relative to the mounting fixture about a horizontal
3 axis orthogonal to a longitudinal axis of the arm.

1 13(previously presented). The shower support according to claim 12,
2 wherein a water conduit passes a pivotable connection of the arm to the
3 mounting fixture.

1 14(previously presented). The shower support according to claim 1,
2 wherein the arm is configured in the form of a fork.

1 15(previously presented). The shower support according to claim 14,
2 wherein the additional shower fixtures are arranged on outer faces of tines of
3 the fork.

Claims 16 and 17 were canceled.